

Technical Details Theatre 2019/2020

General

The room has sloping walls forming a trapezoidal shape narrowing from the front of the room to the stage. Emergency exits for artists are on both sides of the stage. Emergency exits doubling as entrances for the audience are at the front of the room.

Tribune (telescopic): ascending, max. 123 persons
divisible into platforms of 11 seats

Without tribune: max. 250 persons non-seated

Dimensions stage: width: 13,90 meters downstage, 14,40 meters upstage
depth: 8,70 meters
height: 0,60 meters
Playable area between wings/legs and running black:
width: 8,70 meters
depth: 7,00 meters

Clearance: max. 5,10 meters up to static grid
max. 4,50 meters up to spots

Floor: non floating parquet
Marley PVC floor, black

Curtains: running black, divided into 4 parts, 10,00 meters wide, black
2 wings/legs in both sides, can be picked up
horizon back mesh, white

LIGHTING

Controlling: Desk: Zero88 FLX & faderwing
60x CEE-form sockets underneath grid
50x CEE-form sockets in the grid
10x CEE-form sockets on the floor
96x dimmers 3.2 kW EC21 Strand Lightning
9x 10A / 230V fixed voltage CEE-form

Spots (stage): 8x Showtec Infinity iW1915 moving wash
10x ADB pebble 1,0 kW
10x RobertJuliet pebble 1,0 kW
10x RobertJuliet fresnel 1,0 kW
12x RobertJuliet profile 1,0 kW
12x PAR 64 1,0 kW
4x PAR 64 floorcan Shortnose 1,0 kW
6x ETC zoom profile
6x ETC profile 36 deg
2x ETC profile 19 deg
5x fourbar ETC Multipar 575
6x Showtec Striplite
4x Showtec LED Light Bar 16

Spots (hall) 12x Showtec Shark Wash One
1x fourbar ADB profile 650 W
6x ADB pebble 500 W (audience light)

Extra: Swefog Ultimate 300 Haze
Antari 350 fazer

SOUND

PA: 4x Loudspeaker NEEF T121 (12"/1") (2L/2R)
2x Loudspeaker NEEF H18 sub HYBRID 18" L/R
2x Loudspeaker NEEF F15 sub INFRA (center stage)
1x 4ch amplifier LAB GRUPPEN fp10.000Q
1x processor XTA426 (**AES in** | 2x 3way processing | locked)

Monitors 6 x Sound Projects X-Act Active stage monitor

Desks: Digico SD11 (no SD11 "i" version)
including D-stagerack, Cat5e multi, 96 kHz,
28 in – 8 out + 4 AES out (incl. L&R feed)
Mixer FOH+MON combined

Mic's & DI's: 3 x Neumann KM184
2 x AKG C391B
2 x Sennheiser E 908 D
3 x Sennheiser E 604
2 x Sennheiser E 906
1 x Shure Beta 52
1 x Shure Beta 57
2 x Shure 57
1 x Shure SM 94
5 x Shure SM 58
4 x ASL active DI box
1 x BSS AR116 active DI box
1 x Radial Pro D2 stereo DI box
2 x Radial Pro 48 active DI box
1 x Radial Pro AV2 passive stereo DI box

Wireless: 2 x Sennheiser EW500 G3 receiver¹
1 x Sennheiser SKM500 965 handheld¹
1 x Sennheiser SKM500 935 handheld¹
2 x Sennheiser SK500 bodypack with MKE2 lavalier black¹

¹ availability on request

VIDEO

Projection:	Canon XEED WU6010 LCOS LCD projector ¹ ansi lumen: 6000 contrast: 2000:1 resolution: 1920x1200 HDMI/VGA connection (including audio) from cabin or stage right
	Stumpfl projection screen ¹ aspect ratio: 16:9 size: 427 x 240 cm or Full stage projection on horizon back mesh, white ² aspect ratio: 16:9
Controlling:	Roland Edirol V8 mixer ² Numark double DVD player ² Numark triple preview screen ²

EXTRAS

Backline:	Steinway B Grand piano ² (tuning on request) Fender Acoustasonic Junior DSP Combo Amp ² Fender Twin Reverb Amp ² SWR WorkingPro 2x10C Bass Combo Amp ² Peavey KB4 Keyboard Amplifier ²
Power supply	160A for the use of static installation 32A CEE-form upstage-left
Additional	ACS acoustic system (explanation on request) We use a Genie IWP20 vertical mast lift with outreach package, max. height 8,50 meters.

² availability on request

Technical Details Foyer 2019/2020

Dimensions stage: width: 5,50 meters
depth: 3,00 meters
height: 0,20 meters
extra depth; per 1,00 meters

Curtains: running black, divided into 6 parts, black, 4,30 meters high

LIGHTING

Controlling: Showtec 16 channels operating desk

Spots (stage): 6x Showtec Shark Wash One
7x Showtec led pars
4x Briteq adjustable led pc spots

SOUND

PA: 2x SP2 subcabinets active
2x SP2 topcabinets active

Desk: A&H SQ5

Mic's & DI's: shared with theatre; availability depends on theater program

Wireless shared with theater; availability depends on theater program

VIDEO

Projection: Eiki Boardroom projector (2500 ansilumen)
VGA connection from stage right
Scrolldown easyscreen.

CONTACT

Questions: Bart Putman
Technical team leader / Technical production coordinator
bartputman@prins27.nl
+31 (0)6 20735879

* availability on request